



Optional
"H" Trolley
see pg. 9



Standard on 50



STANDARD FEATURES MODELS 15 THRU 50

- Exclusive Precision Block heads (models 15-32), extruded square aluminum heads with rectangular aluminum mount bar (models 40-50).
- Adjustable cushions.
- One piece "C" Trolley standard on models 07-40. "H" trolley optional on models 15-40, "H" trolley standard on Model 50.
- Aluminum sheaves with steel needle bearings.
- Precision aluminum piston.
- Aluminum hard-coated tubes or optional steel tubes (special plating available).
- Nylon coated aircraft type steel cable (heavy duty cable is available).
- Air and oil use up to 150 psi.
- Optional SAE and Metric BSP ports available.
- Optional reed switch package available, see page 10.
- Symmetrically attached sheave bracket can be rotate in 4 directions.

HIGH PRESSURE UNITS AVAILABLE

NOTE: Hydraulic and High Pressure Hydraulic units are equipped with seals that are compatible for most all mineral and petroleum base hydraulic fluids. Consult factory for special fluid compatibility ratings.



MODEL 20P (2 ") FEATURES:

- Hydraulic Service up to 500 PSI Non-shock*.
- Extruded Aluminum Sheaves with ball bearings.
- Extruded Aluminum Sheave Bracket.
- Heavy Duty C Trolley.
- Hard Coated Aluminum or Steel Tube.



MODEL 25P (2 1/2 ") FEATURES:

- Hydraulic Service up to 500 PSI Non-shock*.
 - Heavy Duty "C" Trolley & Sheave-Bracket Assembly
 - Fixed Cushions.
 - Hard-Coated Aluminum or Steel Tube
- *300 PSI maximum for shock or pressure spike applications.